THE ENERGY DOCTOR®
TED
STABILIZERS EXPERTS

Dr. Mansveltkade 48
2242XM Wassenaar
Netherlands
www.tedelectric.eu
0031 6 1988 6240

TED Stabilizer WALL 500-1000VA

- Super slim wall mount design, compact size and space saving.
- Zero cross transfer technology integrated, longer operating life.
- High effciency ultra slim toroidal transformer
- Full protections such as over voltage, under voltage, overload, over temperature, short circuit.
- Selectable Delay Time
- Digital display: input / output voltage, load rate, protection warnings, delay time
- CE / RoHS2.0 certified.





Specifications

Model	TEDWALL500	TEDWALL1000
Power (W)	300W	600W
Input		
Voltage range / Frequency Range	150V ÷ 270V AC / 45-65Hz	
Input Connection	Schuko Power Cord	
Output		
Rated Output Voltage	230V AC	
Output Receptacle	2 x Schuko CEE 7/3	
Precision	±4%	
Frequency Range	50Hz	
Response Time	< 1 second	
Waveform / Power factor	Pure Sine Wave / 0.6	
Efficiency	>96%	
General characteristics		
Protection	Over Voltage / Under Voltage / Overload / Overheat / Short-circuit / Surge	
Ingress Protection / Noise Level	IP20 / <10dB at 1m distance with full load	
Operating Altitude	<1000m	
Dimension D x W x H (mm)	175 x 300 x 72	
Net Weight (kg)	2,63	3,18
Operating Humidity/Temperature	10% - 90%, non-condensing / -15°C ÷ 40°C	

Due to continuous product improvements, program specifications are subject to change without notice