Horus Plus 600

The power keeper

PN: PWUP-LI060H1-AZ01B
EAN: 6422956006419



Specifications

Capacity	600 VA / 360 W
Type	Line Interactive
Input	
Nominal Voltage	230 VAC
Accepted Voltage Range	170-280 VAC
Frequency Range	60/50 Hz (auto sensing)
Output	
Nominal Voltage	230 VAC
AC Voltage Regulation (Batt. Mode)	±10%
Frequency Range (Batt. Mode)	60 Hz or 50 Hz ±1 Hz
Waveform (Batt. Mode)	Simulated Sine Wave
Transfer Time	Typical 2-6 ms
AVR	
Type	2 Boost / 1 Buck
Indicators type	
LCD Display	Input voltage, output voltage, battery capacity, load level and UPS status
Alarm	
Battery Mode	Sounding every 10 seconds
Low Battery	Sounding every second
Overload	Sounding every 0.5 seconds
Fault	Continuously sounding
Protection	
Outlets type	2 x Schuko Battery Backup 2 x RJ11 (IN/OUT) for modem/phone surge protection
Full protection	Over/ under voltage protection, Overload, Discharge and Overcharge Protection

Software Included

Auto-Restart

LCD Touchscreen display

- Touchscreen LCD to display UPS information circularly
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave
- Off-mode charging
- Cold start function
- Software Management (ViewPower)

641.47.25.0

Environement	
Humidity	0-90 % RH @ 0-40°C (non-condensing)
Noise level	Less than 40dB
Device measurement error	± 3%
Battery	
Battery Type & Number	1x GP07122L PN: BTVACEUOATH2LBT01B
Typical Recharge Time	4-6 hours up to 90% capacity
Running time on battery (minutes)	25% Load - 21min 50% Load - 7 min 75% Load - < 2 min 100% Load - < 1 min
Management	
Connection port	USB
Software	https://www.power-software-download.com/viewpower.html
Software capability	Monitor & Control over USB



Physical	
Product dimensions	300 x 101 x 142 mm
Product weight	4.1 kg
Retail Pack Dimensions	344 x 134 x 221 mm
Retail Pack Weight	4.7 kg

Running time on battery



Logistics

Carton Box Size	600 x 362 x 250 mm
Pieces in the Carton Box	4 pcs / ctn
Net & Gross weight / CTN	N.W. / G.W.: 16.4 kg / 18.8 kg

Certificates

RoHS 2011/65/EU CE